

NETGEAR

NETGEAR GS728TXP-300EUS Smart Managed 24-Port Gigabit PoE+ Switch with 4x 10G SFP+ Uplink | 195W PoE Budget Layer 2/3 Lite Enterprise Switch

SKU: 25012889 · EAN: 0606449171068

SPECIFIKAT TEKNIKE**48 specifikat e produktit**

ATRIBUTI	VLERA
Management features	
Switch layer	L2/L3
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	10G Ethernet (100/1000/10000)
SFP+ module slots quantity	4
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	Yes
Port mirroring	Yes
Full duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Spanning tree protocol	Yes
VLAN support	Yes
Virtual LAN features	Voice VLAN
Number of VLANs	256
Data transmission	
MAC address table	16000 entries
Static route	Yes
Number of static routes	32
Packet buffer memory	16 MB

Security	
DHCP features	DHCP client
Access Control List (ACL)	Yes
Access Control List (ACL) ingress	100
IGMP snooping	Yes
MAC address filtering	Yes
SSH/SSL support	Yes
Design	
Rack mounting	Yes
Stackable	Yes
Product colour	Black
Performance	
Built-in processor	Yes
Processor frequency	800 MHz
Flash memory	64 MB
Noise level	26.8 dB
Mean time between failures (MTBF)	1252990 h
Power	
Power consumption (typical)	748.18 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 3000 m
Weight & dimensions	
Width	440 mm
Depth	257 mm
Height	43.2 mm
Weight	3.8 kg
Packaging content	
Cables included	AC

