

APC

APC Smart-UPS / SMT1000iC / Tower / 1000VA / 700W / Line-Interactive / SmartConnect / SmartSlot

SKU: 17013351 · EAN: 0731304332978

SPECIFIKAT TEKNIKE

64 specifikat e produktit

ATRIBUTI	VLERA
Features	
UPS topology	Line-Interactive
Output power capacity	1 kVA
Output power	700 W
Waveform	Sine
Input operation voltage (min)	151 V
Input operation voltage (max)	302 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Surge energy rating	459 J
Response time	10 ms
Output voltage Total Harmonic Distortion (THD)	5%
Noise level	41 dB
Surge protection	Yes
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Auto-restart	Yes
Temperature voltage compensation	Yes
Ports & interfaces	
AC outlet types	C13 coupler, IEC Jumpers
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1

USB port type	USB Type-A
Serial interface	Yes
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	1
SmartSlot	Yes
SmartConnect port	Yes
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery life (max)	5 year(s)
Battery recharge time	3 h
Hot-swap battery	Yes
Automatic battery test	Yes
Cold start	Yes
Replacement battery cartridge	RBC6
Design	
Form factor	Mini Tower
Product colour	Black
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Certificates	
Compliance certificates	RoHS
Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH
Packaging content	
Cables included	RJ-45, USB cable
Management card included	No
Quick installation guide	Yes
Weight & dimensions	
Width	171 mm

Depth	439 mm
Height	219 mm
Weight	18.9 kg
Packaging data	
Package width	328 mm
Package depth	595 mm
Package height	376 mm
Package weight	22.8 kg
Logistics data	
Products per pallet	12 pc(s)
Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	984.74