

ONLINE USV-SYSTEME

# XANTO 3000 Rack UPS 19" – 3000VA Online Double Conversion UPS for Servers & Network Infrastructure

SKU: 26014467 · EAN: 4026908003857

## SPECIFIKAT TEKNIKE

### 51 specifikat e produktit

| ATRIBUTI                       | VLERA                             |
|--------------------------------|-----------------------------------|
| <b>Features</b>                |                                   |
| UPS topology                   | Double-conversion (Online)        |
| Output power capacity          | 3 kVA                             |
| Output power                   | 3000 W                            |
| Waveform                       | Sine                              |
| Input operation voltage (min)  | 110 V                             |
| Input operation voltage (max)  | 300 V                             |
| Input frequency                | 50/60 Hz                          |
| Output operation voltage (min) | 208 V                             |
| Output operation voltage (max) | 240 V                             |
| Output frequency               | 50/60 Hz                          |
| Maximum current                | 17.6 A                            |
| Efficiency                     | 97%                               |
| Emergency Power Off (EPO)      | Yes                               |
| Noise level                    | 50 dB                             |
| Surge protection features      | Fax, Modem, Network               |
| Audible alarm(s)               | Yes                               |
| Management protocols           | SNMP                              |
| Audible alarm modes            | Low battery alarm, Overload alarm |
| <b>Ports &amp; interfaces</b>  |                                   |
| AC outlet types                | C13 coupler, C19 coupler          |
| Power plug                     | C20 coupler                       |
| AC outlets quantity            | 7 AC outlet(s)                    |
| USB port                       | Yes                               |
| USB 2.0 ports quantity         | 1                                 |
| Serial interface               | Yes                               |
| Serial interface type          | RS-232                            |

|                                    |                                                |
|------------------------------------|------------------------------------------------|
| Serial ports quantity              | 1                                              |
| RS-232 ports                       | 1                                              |
| <b>Battery</b>                     |                                                |
| Battery capacity                   | 9 Ah                                           |
| Battery voltage                    | 12 V                                           |
| Number of batteries supported      | 6                                              |
| Typical backup time at full load   | 6 min                                          |
| Typical backup time at half load   | 17 min                                         |
| Battery recharge time              | 4 h                                            |
| Cold start                         | Yes                                            |
| <b>Design</b>                      |                                                |
| Form factor                        | Rackmount/Tower                                |
| Rack capacity                      | 2U                                             |
| Cooling type                       | Active                                         |
| Product colour                     | Black                                          |
| Display type                       | LCD                                            |
| International Protection (IP) code | IP20                                           |
| Mean time between failures (MTBF)  | 50000 h                                        |
| <b>Operational conditions</b>      |                                                |
| Operating temperature (T-T)        | 0 - 40 °C                                      |
| Operating relative humidity (H-H)  | 20 - 90%                                       |
| <b>Certificates</b>                |                                                |
| Certification                      | VFI-SS-111 (EN62040-3)EN62040-1EN62040-2CE     |
| <b>Packaging content</b>           |                                                |
| Cables included                    | Input power cable, Power load cable, USB cable |
| <b>Weight &amp; dimensions</b>     |                                                |
| Width                              | 438 mm                                         |
| Depth                              | 632 mm                                         |
| Height                             | 88 mm                                          |
| Weight                             | 27.5 kg                                        |
| <b>Packaging data</b>              |                                                |
| Package type                       | Box                                            |
| <b>Logistics data</b>              |                                                |
| Harmonized System (HS) code        | 85078000                                       |