

HIKVISION

Kamerë Sigurie IP CCTV Hikvision DS-2CD3T87G3P-LIHSUY/SL, 8MP, 2.8mm, Panoramike, ColorVu 3.0, AcuSense, WDR 130dB, IR dhe Dritë e Bardhë, Audio, PoE+ - Bardhë

SKU: 26028298 · EAN: 6942640547054

SPECIFIKAT TEKNIKE	
33 specifikat e produktit	
ATRIBUTI	VLERA
Camera	
Image sensor	1/2.5" Progressive Scan CMOS
Max. resolution	4256 x 1888 (8 MP)
Min. illumination	Color 0.0005 Lux (F1.0, AGC ON), 0 Lux with light
Shutter time	1 s to 1/100,000 s
WDR	130 dB
SNR	>= 52 dB
Image enhancement	BLC, HLC, 3D DNR
Lens system	
Lens type	Fixed focal, 2.8 mm
Horizontal FOV	182.6°
Vertical FOV	74.6°
Aperture	F1.0
Depth of field	1.6 m to infinity
Night vision	
Supplement light type	White Light + IR
IR wavelength	850 nm
Supplement light range	Up to 40 m
Smart Supplement Light	Yes
Video	
Video compression	H.265+/H.265/H.264+/H.264 (main stream), H.265/H.264/MJPEG (sub-stream)
Max frame rate	20 fps (4256 x 1888)
Video bit rate	32 Kbps to 24 Mbps
Bit rate control	CBR, VBR

Features	
Deep learning	Human and vehicle classification
Smart event	Line crossing, intrusion, region entrance/exit detection
Active deterrence	Strobe light + audible alarm
Audio	
Built-in microphone	Yes
Built-in speaker	Yes
Storage	
On-board storage	MicroSD/SDHC/SDXC, up to 256 GB
Ports & interfaces	
Ethernet	1x RJ45 10/100 Mbps self-adaptive
Power over Ethernet (PoE)	
PoE standard	IEEE 802.3at, Class 4
Power	
Power supply	12 VDC +/-25%
Operational conditions	
Operating temperature	-30°C to 60°C
Protection rating	IP67, NEMA 4X
Design	
Form factor	Fixed bullet
Angle adjustment	Pan 0-360°, tilt 0-90°, rotate 0-360°