

AXIS

Kamerë Sigurie IP CCTV Axis P3925-LRE M12, 1080p, 6 mm, IR, PoE, IP66, IP67, IK10+ - Bardhë

SKU: 26025692 · EAN: 7331021072459

SPECIFIKAT TEKNIKE	
72 specifikat e produktit	
ATRIBUTI	VLERA
Performance	
Type	IP security camera
Placement supported	Indoor
Connectivity technology	Wired
Feature	PTZ control
PTZ modes	Digital PTZ
Feature	Preset points
Feature	Wide Dynamic Range (WDR)
Feature	Day/night mode
Number of languages	11
Languages support	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Korean, Portuguese, Russian
Design	
Mounting type	Ceiling/wall
Product colour	Black, White
Housing material	Aluminium, Tempered glass
International Protection (IP) code	IP66, IP67
IK code	IK10+
Feature	Fog proof
Camera	
Feature	Camera pan control
Feature	Camera tilt control
Minimum illumination	0.02 lx
Angle of rotation	350°
Lens viewing angle. horizontal	56°
Lens viewing angle. vertical	30°
Tilt angle range	0 - 50°

Pan range	-20 - 20°
Camera shutter speed	1/33500 - 2 s
Image sensor	
Number of sensors	1
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")
Feature	Progressive scan
Sensor type	CMOS
Lens system	
Number of lenses	1
Night vision	
Feature	Night vision
Night vision distance	20 m
Infra-red wavelength	850 nm
Video	
Maximum resolution	1920 x 1080 pixels
Total megapixels	2 MP
Video compression formats	AVC, H.264, H.265, HEVC, M-JPEG, MPEG4
Supported graphics resolutions	160 x 120, 160 x 90, 1280 x 960, 1920 x 1080 (HD 1080)
Supported video modes	720p
Frame rate	45 fps
Feature	Video streaming
Image quality adjustment	Brightness, Contrast, Sharpness
Feature	Privacy masking
Feature	Text caption overlay
Feature	Image stabilizer
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Network	
Feature	Ethernet LAN
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.3af, IEEE 802.3at
Feature	Quality of Service (QoS) support
Streaming method	Multicast
Storage	
Feature	Card reader integrated
Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC

Flash memory	512 MB
Security	
Feature	Password protection
Feature	IP address filtering
Security algorithms	802.1x RADIUS
Feature	HTTPS encryption
Alert notification type	E-mail
Power	
Power source type	PoE
Power consumption (typical)	6.3 W
Power consumption (max)	11.8 W
Operational conditions	
Operating temperature (T-T)	-40 - 55 °C
Storage temperature (T-T)	-40 - 65 °C
Operating relative humidity (H-H)	10 - 95%
Weight & dimensions	
Width	160 mm
Depth	116 mm
Height	63 mm
Weight	780 g
Packaging content	
Number of cameras	1
Feature	Manual
Other features	
Doesn't contain	PVC
Logistics data	
Harmonized System (HS) code	85258900