

HUAWEI

Switch Huawei eKitEngine S310-48P4X, 48 porta Gigabit PoE+, 4 porta SFP+ 10G, PoE 380W, 176Gbps, Managed Layer 2+, Rack 1U - Bardhë

SKU: 26031015 · EAN: 6901443450176

SPECIFIKAT TEKNIKE**31 specifikat e produktit**

ATRIBUTI	VLERA
Network	
Switch type	Managed L2+
VLAN support	802.1Q, Port-based, up to 4094 VLANs
Spanning Tree	STP, RSTP, MSTP, ERPS (ITU-T G.8032)
Link aggregation	LACP (up to 128 Eth-Trunk, 8 member ports each)
Multicast	IGMP Snooping
Stacking	iStack, up to 4 switches
Ports & interfaces	
Downlink ports	48 x 10/100/1000BASE-T RJ45 (PoE+)
Uplink ports	4 x 10GE SFP+
Console port	RJ-45
Total ports	52
Power over Ethernet (PoE)	
PoE standard	IEEE 802.3af / IEEE 802.3at
PoE budget	380 W
Performance	
Switching capacity	176 Gbit/s
Packet forwarding rate	131 Mpps
MAC address table	16 000 entries
Security	
Authentication	MAC address, 802.1X, multi-mode
Protection	DHCP Snooping, ARP anti-spoofing, DoS defense, ACL
Management features	
Management	Web GUI, CLI, Telnet, SSHv2, SNMPv1/v2c/v3, Huawei eKit Cloud
Design	

Form factor	1U Rack-mountable
Chassis material	Metal
Weight & dimensions	
Dimensions (H x W x D)	43.6 x 442 x 220 mm
Weight (without packaging)	3.24 kg
Weight (with packaging)	4.29 kg
Power	
Power supply	Built-in AC, 100-240 V, 50/60 Hz
Typical power consumption	49.44 W
Max power consumption (full PoE load)	462.80 W
Static power consumption	34.04 W
Cooling	
Cooling	Air cooling, 2 intelligent fan modules
Operational conditions	
Operating temperature	-5°C to +50°C (0-1800 m altitude)
Storage temperature	-40°C to +70°C
Operating humidity	5% - 95% RH, non-condensing