

APC

APC BX950MI Back-UPS 950VA 520W Line-Interactive UPS with AVR, 6x IEC outlets and USB monitoring – Reliable backup power for PC, NAS & network devices

SKU: 26014924 · EAN: 0731304410805

SPECIFIKAT TEKNIKE

57 specifikat e produktit

ATRIBUTI	VLERA
Features	
UPS topology	Line-Interactive
Output power capacity	0.95 kVA
Output power	520 W
Waveform	Sine
Input operation voltage (min)	140 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	230 V
Output operation voltage (max)	230 V
Output frequency	50/60 Hz
Output frequency regulation	0.5 Hz
Output voltage regulation	10%
Automatic Voltage Regulation (AVR)	Yes
Surge energy rating	273 J
Response time	6 ms
Input power factor	0.54
Noise level	40 dB
Surge protection	Yes
Audible alarm(s)	Yes
Audible alarm modes	Low battery alarm
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
USB port	Yes

USB 2.0 ports quantity	1
USB port type	USB Type-B
Ethernet LAN (RJ-45) ports	2
SmartSlot	No
SmartConnect port	No
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	1 min
Typical backup time at half load	6.5 min
Battery life (max)	2 year(s)
Battery recharge time	8 h
Design	
Form factor	Compact
Cable length	1.2 m
Product colour	Black
LED indicators	Yes
International Protection (IP) code	IP20
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 40 °C
Operating relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Certificates	
Compliance certificates	RoHS
Certification	CB Meet EN62040-1 / CE / IEC-62040-1 / IEC-62040-2
Packaging content	
Cables included	Input power cable
Management card included	No
Manual	Yes
Weight & dimensions	
Width	120 mm
Depth	355 mm
Height	160 mm
Weight	6.1 kg
Packaging data	

Package width	197 mm
Package depth	430 mm
Package height	250 mm
Package weight	6.6 kg
Logistics data	
Harmonized System (HS) code	85078000