

ELO TOUCH SYSTEMS

Monitor 5054L 50-INCH WIDE LCD

SKU: 16008830 · EAN: 0843173156088

SPECIFIKAT TEKNIKE	
62 specifikat e produktit	
ATRIBUTI	VLERA
Display	
Panel type	LCD
LED backlight	Yes
Display diagonal	163.8 cm (64.5")
Display technology	LCD
Display resolution	3840 x 2160 pixels
Display brightness	430 cd/m²
HD type	4K Ultra HD
Touchscreen	Yes
Touchscreen technology	Capacitive
Number of simultaneous touchpoints	40
Multi-touch	Yes
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1100:1
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	1.07 billion colours
Active display area (W x H)	1428.48 x 803.5 mm
Horizontal scan range	30 - 135 kHz
Vertical scan range	24 - 64 Hz
Ports & interfaces	
HDMI ports quantity	2
HDMI version	2.0
DVI port	No
DisplayPorts quantity	1
DisplayPort version	1.4
USB port	Yes

USB ports quantity	2
USB connector type	Mini-USB A, USB Type-A
Ethernet LAN (RJ-45) ports	1
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Interactive flat panel
Placement supported	Indoor
Product colour	Black
VESA mounting	Yes
Panel mounting interface	600 x 600 mm
Performance	
Purpose	Universal
Operating hours (hours/days)	24/7
HDCP	Yes
Power	
Power consumption (typical)	157 W
Power consumption (standby)	0.7 W
Power consumption (sleep)	2 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Weight & dimensions	
Display width	1490.6 mm
Display depth	85.1 mm
Display height	865.5 mm
Display weight	50 kg
Packaging data	
Package width	1750 mm
Package depth	1150 mm
Package height	280 mm
Package weight	60 kg
Packaging content	
Cables included	AC, USB

Operational conditions	
Operating temperature (T-T)	0 - 35 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 95%
Certificates	
Certification	UL, FCC, cUL, IC (Canada), CB, CE, VCCI, RCM, CCC/CEL, China RoHS, NOM, UL60950, IK07
Network	
Ethernet LAN	Yes
Wi-Fi	No
Technical details	
Sustainability certificates	ENERGY STAR