

NETALLY

Z NetAlly LinkRunner AT 3000 Testues Automatik i Rrjetit

SKU: 11006525 · EAN: 0841969101342

SPECIFIKAT TEKNIKE	
27 specifikat e produktit	
ATRIBUTI	VLERA
Features	
Product type	PoE tester
Test type	PoE testing, Transmission testing
Supported connectors	RJ-45, SFP, SFP+
Built-in display	Yes
Display type	LCD
Display diagonal	12.7 cm (5")
Backlight display	Yes
Product colour	Green
RJ-45 ports quantity	1
Fiber mode structure	Multi-mode
LED indicators	Battery level
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3u, IEEE 802.3z
Easy to use	Yes
On/off switch	Yes
Power	
Battery type	Built-in battery
Battery voltage	3.63 V
Charging time	180 min
Certificates	
Compliance certificates	Electromagnetic Compatibility (EMC), Federal Communications Commission (FCC)
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Operating relative humidity (H-H)	75 - 90%
Storage temperature (T-T)	-20 - 60 °C
Weight & dimensions	
Width	102 mm

Depth	42 mm
Height	196 mm
Weight	480 g
Battery	
Battery technology	Lithium-Ion (Li-Ion)
Logistics data	
Country of origin	United States