

AXIS

Axis Netzwerkkamera Bullet Mini M2035-LE HDTV 1080p

SKU: 11006531 · EAN: 7331021072961

SPECIFIKAT TEKNIKE	
69 specifikat e produktit	
ATRIBUTI	VLERA
Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
PTZ modes	Digital PTZ
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Infrared (IR) cut-off filter	Yes
Number of languages	12
Languages support	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian
Certification	CISPR 24, CISPR 35, EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A
Design	
Form factor	Bullet
Mounting type	Ceiling/wall
Product colour	White
Housing material	Aluminium, Plastic
International Protection (IP) code	IP66, IP67
IK code	IK08
Weatherproof	Yes
Camera	
Minimum illumination	0.16 lx
Camera shutter speed	1/19000 - 1/5 s
Image sensor	
Number of sensors	1
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")
Progressive scan	Yes

Sensor type	CMOS
Lens system	
Zoom capability	Yes
Number of lenses	1
Night vision	
LED type	IR
Video	
Maximum resolution	1920 x 1080 pixels
Total megapixels	2 MP
Video compression formats	H.264, H.265
Supported graphics resolutions	1280 x 960
Supported video modes	1080p
Video recording	Yes
Frame rate	30 fps
Flip & mirror	Yes
Privacy masking	Yes
Text caption overlay	Yes
Network	
Ethernet LAN	Yes
Networking standards	IEEE 802.1x, IEEE 802.3af, IEEE 802.3at
Supported network protocols	IPv4, IPv6 USGv6, HTTP, HTTPSb , HTTP/2, TLSb , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP® , SNMP v1/v2c/v3 (MIB-II), DNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, DHCPv4/v6, SOCKS, SSH, LLDP, MQTT v3.1.1
Wi-Fi	No
Bluetooth	No
Quality of Service (QoS) support	Yes
Storage	
Built-in HDD	No
Built-in SSD	No
Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
Flash memory	512 MB
Internal memory	1024 MB
Security	
Password protection	Yes
Video motion detection	Yes
Active tampering alarm	Yes

IP address filtering	Yes
Security algorithms	256-bit AES-XTS, EAP-TLS
HTTPS encryption	Yes
Alert notification type	E-mail
Pixel counter	Yes
Digest authentication	Yes
Power	
Power source type	PoE
Power consumption (typical)	5 W
Power consumption (max)	12.9 W
Operational conditions	
Operating temperature (T-T)	-30 - 50 °C
Storage temperature (T-T)	-40 - 65 °C
Operating relative humidity (H-H)	10 - 100%
Storage relative humidity (H-H)	5 - 95%
System requirements	
Windows operating systems supported	Yes
Weight & dimensions	
Diameter	10.1 cm
Length	170 mm
Weight	491 g
Packaging content	
Number of cameras	1
Other features	
Doesn't contain	BFR, PVC