

NETGEAR

Switch NETGEAR 16P Netgear GS316PP RM PoE+

SKU: 25013083 · EAN: 0606449146912

SPECIFIKAT TEKNIKE	
44 specifikat e produktit	
ATRIBUTI	VLERA
Management features	
Switch type	Unmanaged
Quality of Service (QoS) support	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	16
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
10G support	No
Full duplex	Yes
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-sensing	Yes
Auto-negotiation	Yes
Data transmission	
Switching capacity	32 Gbit/s
MAC address table	4000 entries
Latency (1 Gbps)	3.7 μs
Jumbo frames support	Yes
Jumbo frames	9216
Packet forwarding rate (1 Gbps)	1448000 pps
Packet buffer memory	1 MB
Security	
Queue scheduling algorithms	Weighted Round Robin (WRR)
Design	
Rack mounting	No

Product colour	Black
Housing material	Metal
LED indicators	Activity, Link, PoE, Power, Speed
Wall mountable	Yes
Performance	
Mean time between failures (MTBF)	2362192 h
Power	
DC input voltage	54 V
Input current	3.7 A
Power consumption (max)	195.9 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	16
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	183 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 90%
Operating altitude	0 - 3000 m
Heat dissipation	669.9 BTU/h
Weight & dimensions	
Width	286 mm
Depth	102 mm
Height	27 mm
Weight	880 g
Certificates	
Certification	CE, FCC Part A, IC A, RCM, VCCI, BSMI, KC, CB, CE LVD
Logistics data	
Harmonized System (HS) code	85176990