

CISCO

Switch Cisco Catalyst 9300L Mini C9300LM-48U-4Y-E, 48x Gigabit Ethernet UPOE, 4x 25G SFP28, PoE 790W, Switching Capacity 296Gbps, StackWise-320, Network Essentials, Rackmount 1U - Hiri

SKU: 26030525 · EAN: 0889728429832

SPECIFIKAT TEKNIKE	
37 specifikat e produktit	
ATRIBUTI	VLERA
Management features	
Switch type	Managed
Feature	Quality of Service (QoS) support
Feature	Web-based management
Feature	ARP inspection
Feature	Configuring Location Settings (CLI)
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	48
Basic switching RJ-45 Ethernet ports type	10G Ethernet (100/1000/10000)
Gigabit Ethernet (copper) ports quantity	40
2.5G Ethernet (copper) ports quantity	4
10G Ethernet (copper) ports quantity	8
QSFP+ module slots quantity	2
Network	
Feature	10G support
Feature	VLAN support
Number of VLANs	4094
Data transmission	
Switching capacity	472 Gbit/s
Forwarding rate	327.36 Mpps
MAC address table	32000 entries
Feature	Jumbo frames support
Jumbo frames	9198
Security	
DHCP features	DHCP snooping

Feature	Access Control List (ACL)
Access Control List (ACL) rules	5120
Multicast features	
Feature	Multicast support
Multicast MAC address table	1000 entries
Design	
Feature	Rack mounting
Feature	Stackable
Product colour	Grey
LED indicators	Yes
Market segment	Business
Performance	
Internal memory	8000 MB
Flash memory	16000 MB
Power	
Power source	AC
Feature	Power supply included
Power over Ethernet (PoE)	
Feature	Power over Ethernet (PoE)
Operational conditions	
Operating temperature (T-T)	-5 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 90%