

ASUSTOR

NAS Asustor Drivestor 4 Pro Gen2 AS3304T v2 4-Bay

SKU: 24001525 · EAN: 4710474831524

SPECIFIKAT TEKNIKE	
61 specifikat e produktit	
ATRIBUTI	VLERA
Storage	
Supported storage drive interfaces	Serial ATA III
Storage drive sizes supported	2.5,3.5"
RAID support	Yes
RAID levels	0, 1, 5, 6, 10, JBOD
Hot-swap drive bays	Yes
Supported file systems	BTRFS, FAT32, HFS+, NTFS, exFAT, ext3, ext4
Number of storage drives supported	4
Supported storage drive types	HDD & SSD
Processor	
Processor manufacturer	Realtek
Processor family	Realtek
Processor model	RTD1619B
Processor frequency	1.7 GHz
Processor cores	4
Memory	
Internal memory	2 GB
Internal memory type	DDR4
Flash memory	8192 MB
Network	
Ethernet LAN	Yes
Ethernet LAN data rates	100,1000,2500 Mbit/s
Jumbo frames support	Yes
iSCSI support	Yes
Wake-on-LAN ready	Yes
Supported network protocols	CIFS / SMB, SMB 2.0 / 3.0, AFP, NFS, FTP (Unicode Supported), TFTP, WebDAV, Rsync, SSH, SFTP, iSCSI/IP-SAN, HTTP, HTTPS, Proxy, SNMP, Syslog

Ports & interfaces	
USB port	Yes
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
Ethernet LAN (RJ-45) ports	1
Design	
Cooling type	Active
Product colour	Black
Number of fans	1 fan(s)
Fan diameter	12 cm
LED indicators	Yes
Performance	
Type	NAS
Device class	Home & Home Office
Backup function	Yes
Backup features	Cloud
Number of users	4096 user(s)
Noise level (idle)	19.7 dB
Web-based management	Yes
Share folder access right management	Yes
Security algorithms	256-bit AES, HTTPS, SSH, SSL/TLS
Access Control List (ACL)	Yes
Built-in UPnP AV media server	Yes
Browser supported	Microsoft Edge, Firefox, Chrome
Software	
Operating system installed	ADM
Operating system version	4.1
Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows Vista, Windows XP
Linux operating systems supported	Yes
Mac operating systems supported	Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Server operating systems supported	Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows Server 2016, Windows Server 2019, Windows Server 2022
Other operating systems supported	FreeBSD, UnixWare
Power	
Power supply location	Built-in

Power supply unit (PSU) capacity	90 W
Number of power supply units	1
Power consumption (typical)	25.1 W
AC input voltage	100 - 240 V
Weight & dimensions	
Width	174 mm
Depth	230 mm
Height	170 mm
Weight	2.2 kg
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	5 - 95%
Other features	
Certification	FCC, CE, VCCI, BSMI, C-TICK, KCC, BIS, CCC