

PHILIPS

Monitor Philips 27B2N3200A, 27", FHD IPS, 120Hz, 4ms, HDMI+DP+VGA - Zezë

SKU: 16011557 · EAN: 8721038010527

SPECIFIKAT TEKNIKE	
106 specifikat e produktit	
ATRIBUTI	VLERA
Display	
Display diagonal	68.6 cm (27")
Display resolution	1920 x 1080 pixels
HD type	Full HD
Native aspect ratio	16:9
Display technology	LCD
Panel type	IPS
Feature	LED backlight
Backlight type	W-LED
Display brightness (typical)	350 cd/m ²
Response time	4 ms
Response time measurement type	GTG (Gray to Gray)
Feature	Anti-glare screen
Screen shape	Flat
Contrast ratio (typical)	1500:1
Maximum refresh rate	120 Hz
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	16.7 million colours
Pixel pitch	0.3114 x 0.3114 mm
Pixel density	82 ppi
Vertical scan range	48 - 75 Hz
Viewable size. horizontal	59.8 cm
Viewable size. vertical	33.6 cm
Display diagonal (metric)	68.6 cm
Feature	DDC/CI
Haze rate	25%

Surface hardness	3H
Colour depth	8 bit
Colour gamut standard	sRGB, NTSC
sRGB coverage (typical)	102%
NTSC coverage (typical)	92%
Feature	Display sRGB
Display panel size	27 inch / 68.6 cm
Performance	
Feature	VESA Adaptive Sync support
Feature	Flicker-free technology
Feature	Low Blue Light technology
Multimedia	
Number of speakers	2
RMS rated power	4 W
Feature	Built-in speaker(s)
Design	
Market positioning	Business
Product colour	Black
Front bezel colour	Black
Feet colour	Black
Ports & interfaces	
VGA (D-Sub) ports quantity	1
Feature	HDMI
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort out version	1.2
Audio input	Yes
Feature	HDCP
HDCP version	1.4
Ergonomics	
Feature	VESA mounting
Panel mounting interface	100 x 100 mm
Feature	Cable lock slot
Cable lock slot type	Kensington

Feature	Height adjustment
Adjustable height (max)	15 cm
Feature	Pivot
Pivot angle	-90 - 90°
Feature	Swivelling
Swivel angle range	-180 - 180°
Feature	Tilt adjustment
Tilt angle range	-5 - 30°
Feature	On Screen Display (OSD)
Power	
Energy efficiency class (SDR)	C
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	13 kWh
Power consumption (typical)	14.56 W
Power consumption (standby)	0.3 W
Power consumption (off)	0.3 W
Power consumption (PowerSave)	7.8 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m
Non-operating altitude	0 - 12192 m
Weight & dimensions	
Width (with stand)	616 mm
Depth (with stand)	228 mm
Height (with stand)	539 mm
Weight (with stand)	5.24 kg
Width (without stand)	616 mm
Depth (without stand)	46 mm
Height (without stand)	362 mm
Weight (without stand)	3.24 kg

Packaging data	
Package width	690 mm
Package depth	139 mm
Package height	445 mm
Package weight	7.71 kg
Packaging content	
Feature	Stand included
Feature	Manual
Bundled software	SmartControl, SmartManagement
Sustainability	
Doesn't contain	PVC/BFR
Other features	
Compatible operating systems	DDC/CI, Mac OS, sRGB, Windows 11 / 10
Exterior finish type	Textured
Monitor sync input signal	Separate Sync, Sync on Green
User controls	SmartImage, Input, Brightness, Menu, Power On/Off
Picture enhancement	SmartImage
Feature	SoftBlue
Feature	EasyRead mode
Recycling data	
Packaging recyclability rate	100%
Product post-consumer recycled plastic	85%