

SAMSUNG

Smart Board Samsung Flip Pro WM65B / 65"/ 4K UHD VA Multi Touch / 60Hz / 8ms / HDMI+DisplayPort+USB-C - Gri

SKU: 22002746 · EAN: 8806094472493

SPECIFIKAT TEKNIKE	
60 specifikat e produktit	
ATRIBUTI	VLERA
Display	
Display diagonal	165.1 cm (65")
Display brightness	350 cd/m ²
Display resolution	3840 x 2160 pixels
HD type	4K Ultra HD
Panel type	VA
Contrast ratio (typical)	4000:1
Response time	8 ms
Pixel frequency (max)	594 MHz
Display brightness (min)	220 cd/m ²
Touchscreen	Yes
Touch technology	Multi-touch
Touchscreen type	Infrared
Number of simultaneous touchpoints	20
Touch system response time	26 ms
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Pixel pitch	0.372 x 0.372 mm
Colour gamut	72%
Horizontal scan range	30 - 81 kHz
Vertical scan range	48 - 75 Hz
Haze rate	2%
Computer system	
Operating system installed	Tizen
Operating system version	6.5
User memory	32 GB

Network	
Wi-Fi	Yes
Bluetooth	Yes
Ethernet LAN	Yes
Ports & interfaces	
HDCP	Yes
HDCP version	2.2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
HDMI ports quantity	2
USB Type-C ports quantity	1
HDMI version	2.0
DisplayPort version	1.2
DisplayPorts quantity	1
Ethernet LAN (RJ-45) ports	1
Audio output	1
RS-232 ports	1
Ergonomics	
Product colour	Grey, White
VESA mounting	Yes
Panel mounting interface	400 x 400 mm
Frame material	Plastic
Certification	Class A FCC (USA) Part 15, Subpart B KCC/EK (Korea) Tuner : KN32 / KN35 Tunerless : KN32 / KN35 CE (Europe) EN55032 : 2012 or 2015 EN55024:2010 or EN 55035:2017 VCCI (Japan) VCCI CISPR32 :2016 CCC(China) GB/T9254-2008 GB17625.1-2012 BSMI (Taiwan) CNS13438 (ITE EMI) CNS14336-1 (ITE Safety) CNS15663 (RoHS) C-Tick (Australia) AS/NZS CISPR32:2015 GOST(Russia/CIS) ROCT CISPR 24-2013 ROCT CISPR 22:2005
Performance	
Operating hours (hours/days)	12/7
Power	
Power consumption (typical)	192.5 W
Power consumption (standby)	0.5 W
Power consumption (sleep)	0.5 W
AC input voltage	100-240 V
AC input frequency	50/60 Hz
Operational conditions	
Operating temperature (T-T)	0 - 40 °C

Operating relative humidity (H-H)	10 - 80%
Weight & dimensions	
Width	1522.4 mm
Depth	62.9 mm
Height	897.6 mm
Weight	39.7 kg
Bezel width	2.62 cm
Packaging data	
Package width	1691 mm
Package depth	198 mm
Package height	1055 mm
Package weight	48.2 kg