

EIZO

EIZO 48.3cm (19") S1934H-BK 5:4 DVI+DP LED IPS Lift bl.

SKU: 16008965 · EAN: 4995047049234

SPECIFIKAT TEKNIKE	
90 specifikat e produktit	
ATRIBUTI	VLERA
Display	
Display diagonal	48.3 cm (19")
Display resolution	1280 x 1024 pixels
HD type	SXGA
Native aspect ratio	5:4
Display technology	LCD
Panel type	IPS
LED backlight	Yes
Backlight type	W-LED
Touchscreen	No
Display brightness (typical)	250 cd/m ²
Response time	14 ms
Anti-glare screen	Yes
Screen shape	Flat
Supported graphics resolutions	1280 x 1024 (SXGA)
Contrast ratio (typical)	1000:1
Maximum refresh rate	60 Hz
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	16.78 million colours
Pixel pitch	0.293 x 0.293 mm
Pixel density	87 ppi
Horizontal scan range	31 - 64 kHz
Vertical scan range	55 - 61 Hz
Viewable size. horizontal	37.5 cm
Viewable size. vertical	30 cm
Viewable size diagonal	48.1 cm
Colour gamut standard	sRGB

Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Low Blue Light technology	Yes
Multimedia	
Number of speakers	2
Built-in speaker(s)	Yes
Built-in camera	No
Design	
Market positioning	Office
Product colour	Black
Feet colour	Black
Ports & interfaces	
Built-in USB hub	No
VGA (D-Sub) ports quantity	1
DVI port	Yes
DVI-D ports quantity	1
HDMI	No
DisplayPorts quantity	1
Headphone out	Yes
Headphone outputs	1
Headphone connectivity	3.5 mm
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot	No
Height adjustment	Yes
Adjustable height (max)	10 cm
Pivot	Yes
Pivot angle	0 - 90°
Swivelling	Yes
Swivel angle range	-35 - 35°
Tilt adjustment	Yes
Tilt angle range	0 - 30°

On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Swedish
Number of OSD languages	9
Power	
Energy efficiency class (SDR)	C
Energy consumption (SDR) per 1000 hours	9 kWh
Power consumption (typical)	9.4 W
Power consumption (standby)	0.5 W
Power consumption (max)	21 W
Power consumption (off)	0.1 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	405 mm
Depth (with stand)	205 mm
Height (with stand)	506.5 mm
Weight (with stand)	5.6 kg
Width (without stand)	405 mm
Depth (without stand)	61.5 mm
Height (without stand)	334 mm
Weight (without stand)	3.8 kg
Packaging content	
Stand included	Yes
Cables included	AC, Audio (3.5mm), DVI, VGA
Quick start guide	Yes
Sustainability	
Sustainability certificates	ENERGY STAR
Other features	
Automatic brightness control	Yes

Warranty period	5 year(s)
Look-up table (LUT) bit depth	10
Certification	TCO, TUV/GS, RCM, CE, CB, cTUVus, FCC-B, ICES-003-B, TUV/S, VCCI-B, EPA Energy Star, RoHS, WEEE, RoHS, CCC, EAC
Logistics data	
Harmonized System (HS) code	85285210