

ASUSTOR

NAS ASUSTOR Drivestor 4 Gen 2 AS1204T / 4-Bay

SKU: 24001540 · EAN: 4710474831944

SPECIFIKAT TEKNIKE	
63 specifikat e produktit	
ATRIBUTI	VLERA
Storage	
Storage drive interface	Serial ATA
Storage drive sizes supported	3.5"
RAID support	Yes
RAID levels	0, 1, JBOD
Online RAID migration	Yes
Supported file systems	FAT32, HFS+, NTFS, exFAT, ext3, ext4
Storage drives installed	No
Total installed storage capacity	0 TB
Number of storage drives supported	4
Installed storage drive type	No
Supported storage drive types	HDD & SSD
Bad block scan	Yes
Processor	
Processor manufacturer	Realtek
Processor family	Realtek
Processor model	RTD1619B
Processor frequency	1.7 GHz
Processor cores	4
Memory	
Internal memory	1 GB
Internal memory type	DDR4
Flash memory	8000 MB
Network	
Ethernet LAN	Yes
Ethernet LAN data rates	100,1000,2500 Mbit/s
DHCP server	Yes
Jumbo frames support	Yes

iSCSI support	Yes
Wake-on-LAN ready	Yes
Supported network protocols	Supported), TFTP, WebDAV, Rsync, SSH, SFTP, iSCSI/IP-SAN, HTTP, HTTPS, Proxy, SNMP, Syslog
Ports & interfaces	
USB port	Yes
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
Ethernet LAN (RJ-45) ports	1
Design	
Chassis type	Tower
Cooling type	Active
Product colour	Black
Number of fans	1 fan(s)
Fan diameter	12 cm
LED indicators	Yes
Performance	
Type	NAS
Device class	Home & Home Office
Backup function	Yes
Number of users	4096 user(s)
Noise level	19.7 dB
Snapshot	Yes
Web-based management	Yes
Security algorithms	256-bit AES, HTTPS, SNMP, SSH
Access Control List (ACL)	Yes
Browser supported	Firefox, Chrome, Safari, Microsoft Edge
System log	Yes
S.M.A.R.T. support	Yes
Software	
Operating system installed	ADM
Operating system version	5.0
Windows operating systems supported	Windows 10, Windows 11
Linux operating systems supported	Yes
Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019, Windows Server 2022
Power	

Power supply unit (PSU) capacity	65 W
Power consumption (typical)	22.8 W
AC input voltage	100 - 240 V
Weight & dimensions	
Width	164 mm
Depth	218 mm
Height	165 mm
Weight	1.57 kg
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	5 - 95%
Storage temperature (T-T)	-20 - 70 °C